STEEL GRINDING WHEELS

Product Description

Abrasive : Aluminum Oxide (EKR)

Features : Available in 36, 46 and 60 grit size, it is used for cylindrical and surface grinding in addition to general purpose usage. It is mainly used for grinding tool steel and unhardened steels. High performance and long lasting. Maximum peripheral speed 35 m/s.

Type	Specification	Dimension *(mm)*	Peripheral Speed *(m/s)*	Shirink	Barkod / **Article**
T1	EKR 36 K6V	**150** x 20 x20	35	5	869149**914450**8
		175 x 20 x20		5	869149**914480**5
		250 x 25 x76.2		5	869149**914490**4
		250 x 30 x76.2		3	869149**914520**8
		250 x 32 x76.2		3	869149**914770**7
		250 x 40 x76.2		2	869149**914560**4
		300 x 40 x127		2	869149**914590**1
		350 x 40 x127		2	869149**914640**3
		350 x 50 x127		1	869149**914670**0
		400 x 40 x127		1	869149**914700**4
		400 x 50 x127		1	869149**908902**1
	EKR 46 K6V	**150** x 20 x20	35	5	869149**914460**7
		175 x 20 x20		5	869149**914730**1
		200 x 20 x20		5	869149**914750**9
		250 x 25 x76.2		5	869149**914500**0
		250 x 30 x76.2		3	869149**914530**7
		250 x 32 x76.2		3	869149**914780**6
		250 x 40 x76.2		2	869149**914570**3
		300 x 40 x76.2		2	869149**914620**5
		300 x 40 x127		2	869149**914600**7
		350 x 40 x127		2	869149**914650**2
		350 x 50 x127		1	869149**914680**9
		400 x 35 x127		1	869149**916000**3
		400 x 40 x127		1	869149**914710**3
		400 x 50 x127		1	869149**903804**3
	EKR 60 K6V	**150** x 20 x20	35	5	869149**914470**6
		175 x 20 x20		5	869149**914740**0
		200 x 20 x20		5	869149**914760**8
		250 x 25 x76.2		5	869149**914510**9
		250 x 30 x76.2		3	869149**914540**6
		250 x 32 x76.2		3	869149**914550**5
		250 x 40 x76.2		2	869149**914580**2
		300 x 40 x76.2		2	869149**914630**4
		300 x 40 x127		2	869149**914610**6
		350 x 40 x127		2	869149**914660**1
		350 x 50 x127		1	869149**914690**2
		400 x 40 x127		1	869149**914720**8
		400 x 50 x127		1	869149**903805**0